
Subject: help with irc

Posted by [Dean20056](#) on Sun, 07 Oct 2007 19:23:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

hi there i was wondering if anyone has a irc bot/script that will set people what i tell it to the bot will be channel owner and will set me +q in the chan. and in the other 2 chans aswell it will do the same for other people i tell it to like aohv in all 3 chans lol. i have asked a few people but some did not know and some busy. us there anyone what know how i can make this?

Subject: Re: help with irc

Posted by [BlueThen](#) on Sun, 07 Oct 2007 19:29:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

Are you wanting the bot to set people owner in any chan you want? Because that's not possible unless you are a irc op...

Subject: Re: help with irc

Posted by [danpaul88](#) on Sun, 07 Oct 2007 19:30:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

Why not just register the channel and give the people auto-op / hop / voice status? It's built right into IRC...

/cs register <#channel> <password> <description>

/cs aop <#channel> add <person>

Subject: Re: help with irc

Posted by [Rev](#) on Sun, 07 Oct 2007 21:52:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

danpaul88 wrote on Sun, 07 October 2007 15:30 Why not just register the channel and give the people auto-op / hop / voice status? It's built right into IRC...

/cs register <#channel> <password> <description>

/cs aop <#channel> add <person>

Because chanserv can only set one person +q unless you use access. which is what he should use

/cs access (channel) add (person) (level)

Subject: Re: help with irc

Posted by [BlueThen](#) on Sun, 07 Oct 2007 22:01:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

...or

/mode channel +q person

Subject: Re: help with irc

Posted by [Lone0001](#) on Mon, 08 Oct 2007 06:25:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

Or give the person the pass to the chan if you registered it and they can just get it theirself

/cs identify <Channel> <Pass>

and use chanserv for the other ops ie. op,voice,ao,halfop etc...

Subject: Re: help with irc

Posted by [Dean20056](#) on Thu, 11 Oct 2007 00:34:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

hi this is what i was looking for lol i found it incase any of you want it and are intrested this is it.

```
on *:Load: {
    set %modchan $?="State your channel for the modlist:"
    echo -a Modlist now applys to %modchan
    if ($?!="Turn reverse rawmodes for modlist on?") {
        set %reverseraw 1
        echo -a reverse rawmodes on
    }
    else {
        unset %reverseraw
        echo -a reverse rawmodes off
    }
}
```

```
on *:Unload: {
    unset %modchan
    unset %reverseraw
}
```

```
menu status,channel {
    -
    Modlist
```

```

.Change modlist channel {
    set %modchan $?="State your channel for the modlist:"
    echo -a Modlist now applies to %modchan
}
.Reverse rawmodes on/off {
    if ($?!="Turn reverse rawmodes for modlist on?") {
        set %reverseraw 1
        echo -a reverse rawmodes on
    }
    else {
        unset %reverseraw
        echo -a reverse rawmodes off
    }
}
-
}

on *:TEXT:*:%modchan: {
if ($1 == !amod) && ($3) && ($left($nick(#,$me).pnick,1) == ~) {
    writeini modlist.ini modlist $2 $3
    msg # 12 $2 is added to the modlist as: + $+ $3
}
if ($1 == !dmod) && ($2) && ($left($nick(#,$me).pnick,1) == ~) {
    remini modlist.ini modlist $2
    msg # 4 $2 has been removed from the modlist
}
elseif ($1 == !amod || $1 == !dmod) && ($left($nick(#,$me).pnick,1) != ~) {
    .notice $nick you dont have access to use this command
}
if ($1 == !modlist) && ($nick !isop #) { .notice $nick you dont have access to use this command }
elseif ($1 == !modlist) && ($nick isop #) {
    var %line 2
    while ($read(modlist.ini, %line)) {
        if (q isin $gettob($read(modlist.ini, %line),2,61)) && ($gettob($read(modlist.ini, %line),1,61)
!isin %qnicks) {
            var %qnicks $addtok(%qnicks,$chr(32) $gettob($read(modlist.ini, %line),1,61),44)
        }
        inc %line
    }
    var %line 2
    while ($read(modlist.ini, %line)) {
        if (a isin $gettob($read(modlist.ini, %line),2,61)) && ($gettob($read(modlist.ini, %line),1,61)
!isin %qnicks %anicks) {
            var %anicks $addtok(%anicks,$chr(32) $gettob($read(modlist.ini, %line),1,61),44)
        }
        inc %line
    }
    var %line 2
}
}

```

```

while ($read(modlist.ini, %line)) {
    if (o isin $gettوك($read(modlist.ini, %line),2,61)) && ($gettوك($read(modlist.ini, %line),1,61)
!isin %qnicks %anicks %onicks) {
        var %onicks $addtok(%onicks,$chr(32) $gettوك($read(modlist.ini, %line),1,61),44)
    }
    inc %line
}
var %line 2
while ($read(modlist.ini, %line)) {
    if (h isin $gettوك($read(modlist.ini, %line),2,61)) && ($gettوك($read(modlist.ini, %line),1,61)
!isin %qnicks %anicks %onicks %hnicks) {
        var %hnicks $addtok(%hnicks,$chr(32) $gettوك($read(modlist.ini, %line),1,61),44)
    }
    inc %line
}
var %line 2
while ($read(modlist.ini, %line)) {
    if (v isin $gettوك($read(modlist.ini, %line),2,61)) && ($gettوك($read(modlist.ini, %line),1,61)
!isin %qnicks %anicksn %onicks %hnicks %vnicks) {
        var %vnicks $addtok(%vnicks,$chr(32) $gettوك($read(modlist.ini, %line),1,61),44)
    }
    inc %line
}
msg # 4~Owners: %qnicks
msg # 7&Admins: %anicks
msg # 8@Ops: %onicks
msg # 9 $+ $chr(37) $+ Half-ops: %hnicks
msg # 13+Voice: %vnicks
}
}

on *:JOIN:%modchan:{ 
if ($readini(modlist.ini,n,modlist,$nick)) {
    set -e %checkmod 1
    who $nick
}
}

raw 352:*:{ 
if (%checkmod) { 
    $iif(r !isincs $7, msg %modchan $6 $+ $chr(44) register with nickserv and hop to get your + $+
$readini(modlist.ini,n,modlist,$6), mode %modchan + $+ $readini(modlist.ini,n,modlist,$6)
$str($chr(32) $6,$len($readini(modlist.ini,n,modlist,$6))))
    unset %checkmod
}
}

on !*:RAWMODE:%modchan:{ 

```

```

if ($left($nick(#,$nick).pnick,1) != ~) && ($nick != Chanserv) && (%reverseraw) {
    var %rawl 1
    var %rawlen $len($1)
    while ($mid($1,%rawl,1)) && (%rawlen > 0) {
        if ($mid($1,%rawl,1) == +) || ($mid($1,%rawl,1) == -) { var %rawmodesdone
$addtok(%rawmodesdone,$replacex($mid($1,%rawl,1),+,-,-,+),0) }

        while ($mid($1,%rawl,1)) && ($mid($1,%rawl,1) != +) && ($mid($1,%rawl,1) != -) {
            if ($calc($count($1,$mid($1,%rawl,1))/2) != $round($count($1,$mid($1,- $+ %rawl,1))/2),0))
&& ($mid($1,%rawl,1) !isin %rawmodesdone) {
                var %rawmodesdone $addtok(%rawmodesdone,$mid($1,%rawl,1),0)
                inc %rawl
                dec %rawlen
            }
        }
        inc %rawl
        dec %rawlen
    }
    if %rawmodesdone { mode # %rawmodesdone $2- }
}
}

```

It goes into your bots remoteds and u type !amod <nick> <level> like !add EKT-Dean qaohv and that would make them +q. but the bot must be +q in the channel for it to work.
